

## Air-Ride Combination Low-Loader

The Air-ride combination Low-Loader Tracking Trailer is towed by a 4x4 vehicle. More Suited for Smaller Hero Cars.

The suspension is 100% air cushion and can be adjusted according to weight and ride comfort.

For crew comfort all of our Low Loaders have a weatherproof and safe crew compartment area with bench seating and safety harnesses for 6 crew members.

The Low Loader is Driven by one of our Precision Tracking Vehicle Drivers and if used as Tracking Vehicle and Low Loader Combination – 2 Man Crew is required for its operation and Rigging.



Standard Equipment	Optional Equipment
Safety Harnesses	Scaffold Tube and Fittings Rig
Lap belts in Crew Compartment	5K Generator
Dimensions / Weights	
Overall Length of Towing Vehicle and Trailer	13m
Width of Low Loader	2.55m
Height of Low Loader	2.8m
Working Deck of Low Loader	5.3m x 2.55m
Cheyenne Tracking Vehicle Length	6.5m
Cheyenne Width	2.2m
Cheyenne Working Deck	2.4mx 2.2m
Gross Train Weight of Tow Vehicle and Trailer	7000kg

For more information,  
please contact us.

**Web**

[www.bickers.co.uk](http://www.bickers.co.uk)

**Email**

[action@bickers.co.uk](mailto:action@bickers.co.uk)