

Combination Low Loader Tracking Trailer

Our Combination Low Loading Tracking Trailers – these are marginally smaller than the No.1, but their advantage is they are towed by one of our Tracking Vehicles. The suspension is 100% air cushion on No2 and can be adjusted according to weight and ride comfort. No4 is non-air at the rear however has a higher weight carrying capacity. Tracking Vehicle can be split from the low loader trailer, for use as separate tracking vehicle. These are the only Combination Tracking Vehicles / Low Loaders covering General Tracking, Small Camera Crane work, A Frame and Low Loader work in Europe

For crew comfort all our Low Loaders have a weather proof and safe crew compartment area with bench seating and safety harnesses for 6 crew members.



Standard Equipment	Optional Equipment
Safety Harnesses	Scaffold Tube and Fittings Rig
Lap belts in Crew Compartment	5K Generator
Dimensions / Weights	
Overall Length of Towing Vehicle and Trailer	13m
Width of Low Loader	2.55m
Height of Low Loader	2.8m
Working Deck of Low Loader	5.3m x 2.55m
Cheyenne Tracking Vehicle Length	6.5m
Cheyenne Width	2.2m
Cheyenne Working Deck	2.4mx 2.2m
Gross Train Weight of Tow Vehicle and Trailer	7000kg

For more information,
please contact us

Web

www.bickers.co.uk

Email

action@bickers.co.uk